

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY Type S Hydrated Lime Putty
(Ca(OH)₂ * Mg(OH)₂)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name and Address

Chemical Lime Company
3724 Hulen Street
Fort Worth, Texas 76107

Emergency Telephone Number

Chemtrec 800-424-9300

Information Phone Number

817-732-8164

Date Prepared

11/18/2004

Section II - Hazardous Ingredients/Identity Information

Hazardous Components	CAS	Common Name	OSHA PEL	ACGIH TLV	Other Limits	% (optional)
Calcium hydroxide	1305-62-0	Hydrated Lime	5 mg/m3	5 mg/m3	7340 mg/kg	<40%
Magnesium hydroxide	1309-42-8	Brucite	N.A.	N.A.		<25%
Magnesium oxide	1309-48-4	Periclase	10 mg/m3	10 mg/m3	6 mg/m3	<5%
Calcium carbonate	1317-65-3	Limestone	15 mg/m3	10 mg/m3	6450 mg/kg	<3%
Silicon dioxide	14808-60-7	Quartz	*see note below	0.1 mg/m3	4 mg/m3	<2%

*SiO₂ OSHA PEL: 10 mg/m3 divided by (the percentage of silica in the dust plus 2) (respirable)

Section III - Physical/Chemical Characteristics

Boiling Point	100 °C	Melting Point	dec. 580 °C	Specific Gravity	1.35 - 1.4 g/cc
Vapor Pressure (mm Hg)	N.A.	Vapor Density	N.A.	Evaporation Rate	N.A.
Solubility in Water	Material is a stable suspension of calcium magnesium hydroxide in water. pH=12.4@25°C				
Appearance and Odor	White high viscosity putty, odorless				

Section IV - Fire and Explosion Hazard Data

Flash Point	LEL/UEL	Flammable Limits	Extinguishing Media
N.A.	N.A.	N.A.	Not Combustible -- Use extinguishing agent for surrounding fire

Special Firefighting Procedures/Unusual Fire and Explosion Hazards

Avoid skin contact or inhalation of dust if material becomes dry.

Section V - Reactivity Data

Stability	Conditions to Avoid (stability - related)
Stable	Material is stable

Incompatibility (Materials to Avoid)

Acids: Reacts vigorously and produces heat. Maleic Anhydride: May react explosively. Nitro Organic Compounds: May react to form explosive salts. Phosphorous: May form flammable products when heated. Aluminum: May react to form hydrogen gas.

Hazardous Polymerization/Hazardous Decomposition of Byproducts

Will not occur (none)

Section VI - Health Hazard Data

Route(s) of Entry: Inhalation, Ingestion

Health Hazards (Acute and Chronic)

Avoid skin and eye contact as irritation will occur. Contact lenses should not be worn when working with lime products. Inhalation can cause coughing, sneezing, or breathing problems.

Carcinogenicity:	OSHA?	SiO ₂	NTP/IARC Monographs?	SiO ₂
------------------	-------	------------------	----------------------	------------------

Respirable crystalline silica from occupational sources is classified by IARC as a Group I Carcinogen.

California Proposition 65: Silica is on the Governor's Proposition 65 list. Components used in this product may contain trace amounts of inherent naturally occurring elements (such as, but not limited to arsenic, cadmium) that are on the Governor's Proposition 65 list.

Section VI - Health Hazard Data (continued)**Signs and Symptoms of Exposure**

Skin or eye irritation; coughing or breathing problems.

Medical Conditions Generally Aggravated by Exposure

Respiratory problems, asthma, dermatitis or skin or eye sensitivity.

Emergency and First Aid Procedure

Flush contaminated area with excess water. If eye contact, rinse eye with eye wash solution or excess water and seek medical attention immediately.

Section VII - Precautions for Safe Handling and Use**Steps to be Taken in Case Material is Released or Spilled**

Protect skin and eyes from contact and avoid inhalation of mist. Collect using shovels or other suitable methods and place in steel drums. Keep away from acids or organic materials.

Waste Disposal Method

Carefully add water and flush to sewer. Consult local, state, or federal regulations.

Precautions to be Taken in Handling and Storage

Store in tightly closed containers and keep dry and away from acids or other incompatible substances.

Do not store or ship in aluminum containers.

Other Precautions

Avoid eye contact and breathing dust if material becomes dry.

NFPA Rating: HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

HMIS Rating: HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 0

WHMIS Rating: D2A, E

Section VIII - Control Measures**Respiratory Protection (Specify Type)**

Dust masks meeting the NIOSH N95 rating are sufficient for casual exposure to mist or dust. (42 CFR)

Ventilation	Local Exhaust N.A.	Special	Do not dispose of dust with combustible materials.
	Mechanical (General) N.A.	Other	

Protective Gloves

Clean dry rubber gloves

Other Protective Clothing or Equipment

Full clothing to cover arms and legs, safety glasses or face shield.

Work/Hygienic Practices

Eye wash and shower station should be readily available.

Chemical Lime Company provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person. Individuals receiving this information must consult their own technical and legal advisors and/or exercise their own judgment in determining its appropriateness for a particular purpose. Chemical Lime Company makes no representations or warranties, either express or implied, including without limitation and warranties of merchantability or fitness for a particular purpose with respect to the information set forth herein or the product(s) to which the information refers. Accordingly, Chemical Lime Company will not be responsible or liable for any claims, losses or damages resulting from the use of or reliance upon or failure to use this information.